

# AbsorGel® Hanging-C

TECHNICAL PRODUCT SHEET



## Installation and usage

AbsorGel® Hanging-C starts working as soon as it is removed from its transparent sealed packaging or removed from a box master PE-bag. It is easy to install and remove with our AbsorHook™ System. The optional AbsorStick™ can be attached to the AbsorHook™ to reach the lashing rings. For high cube containers, two Absorsticks can be combined for increased length which means that no ladder is needed, and you will save time, effort and money. It is installed within the corrugated recess of container side panels. AbsorGel® Hanging-C can be also hung horizontally by using the grommet.

The calcium chloride absorbs moisture from the surrounding air passing in through its permeable packaging (DuPont™ Tyvek®). The liquid Calcium Chloride turns into gel by the modified starch.

AbsorGel® Hanging-C is fitted with a AbsorHook™ and adhesive pads to keep it securely in place. AbsorGel® Hanging-C can be used for any type of cargo and only needs 25 mm between the cargo and the AbsorGel® Hanging-C.



## Installation video guidelines

Every box is accompanied with assembly instruction via QR code. Read the code or click it to access the installation video.



## Main features


DESICCANT TYPE	CONTAINER DESICCANT
TYPES AVAILABLE	0,5 kg / 1,0 kg
ABSORBING AGENT	CALCIUM CHLORIDE WITH A PURITY OF >94% MIXED WITH STARCH
MOISTURE ABSORPTION	> 300% UNDER FIELD CONDITIONS*
PERMEABLE MATERIAL	TYVEK®
INSTALLATION MODE	VERTICAL
INSTALLATION ACCESORIES	INTEGRATED HOOK + ABSORSTICK™
CLIMATE IMPACT BEFORE OFFSETTING**	0,78-1,23 kg CO <sub>2</sub> / UNIT

\*ABSORPTION CAPACITY IN FIELDS CONDITIONS DEPENDS ON TEMPERATURE AND RELATIVE HUMIDITY. ABSORPTION CAPACITY IN CLIMATE CHAMBER WITH CONSTANT HIGH TEMPERATURE AND RELATIVE HUMIDITY AND LONG DURATION CAN EXCEED 350%.  
\*\*ABOVE CO<sub>2</sub> HAS BEEN OFFSET THROUGH GOLD STANDARD PROJECTS. READ MORE ABOUT THE OFFSETTING PROGRAMS ON THE WEB.

ABSORPARTNER IN USA



## Installation example



INSTALLATION USING ABSORSTICK™

## Shelf Life and Conditions

The shelf life of this product is three years from the production date printed on the packaging label.

Recommended storage temperature: 5 °C to 25 °C



## Access to the Safety Data Sheet

Read or click the code to access the SDS with technical and regulatory information and the different Exposure Scenarios.



## Product specifications

NAME DESCRIPTION	ABSORGEL®HANGING-C 1,0KG	ABSORGEL®HANGING-C 1,0KG	ABSORGEL®HANGING-C1,0 KG
PART NO	5501102-SP10	5501102-IP2	5501102-IP0
DESICCANT AGENT	CALCIUM CHLORIDE >94%/ STARCH	CALCIUM CHLORIDE >94%/ STARCH	CALCIUM CHLORIDE >94%/ STARCH
DESICCANT AGENT WEIGHT	1,0 kg	1,0 kg	1,0 kg
COUNTRY OF ORIGIN	CHINA	CHINA	CHINA
PERMEABLE MATERIAL	TYVEK®	TYVEK®	TYVEK®
PACKAGING CONFIGURATION	SINGLE PACK	INDUSTRIAL PACK	INDUSTRIAL PACK
CLIMATE IMPACT BEFORE OFFSETTING	1,23 kg CO <sub>2</sub> / UNIT	1,17 kg CO <sub>2</sub> / UNIT	1,16 kg CO <sub>2</sub> / UNIT
CO <sub>2</sub> KG/KG ABSORBING AGENT	1,23	1,17	1,16
<b>INSTALLATION ACCESORIES</b>			
OTHER	INTEGRATED HOOK	INTEGRATED HOOK	INTEGRATED HOOK
ABSORSTICK™	10 PCS	2 PCS	0 PCS
GROMMETS	YES	YES	YES
ADHESIVE PADS	YES	YES	YES
<b>PACKAGING INFORMATION</b>			
<b>BOX</b>			
INNER BAG PCS	1	10	10
BOX PCS	10	10	10
BOX GROSS WEIGHT kg	12,4	12,4	12,4
DIM LX W X H mm	478 X 296 X 233	478 X 296 X 233	478 X 296 X 233
<b>PALLET</b>			
PCS	320	320	320
GROSS WEIGHT kg	403	403	403
DIM LX W X H mm	1120 X 1120 X 1100	1120 X 1120 X 1100	1120 X 1120 X 1100


## Dimensions



## Product specifications

NAME DESCRIPTION	ABSORGEL®HANGING-C 0,5KG	ABSORGEL®HANGING-C 0,5KG	ABSORGEL®HANGING-C 0,5KG
PART NO	5501602-SP15	5501602-IP2	5501602-IP0
DESICCANT AGENT	CALCIUM CHLORIDE >94%/ STARCH	CALCIUM CHLORIDE >94%/ STARCH	CALCIUM CHLORIDE >94%/ STARCH
DESICCANT AGENT WEIGHT	0,5 KG	0,5 KG	0,5 KG
COUNTRY OF ORIGIN	CHINA	CHINA	CHINA
PERMEABLE MATERIAL	TYVEK®	TYVEK®	TYVEK®
PACKAGING CONFIGURATION	SINGLE PACK	INDUSTRIAL PACK	INDUSTRIAL PACK
CLIMATE IMPACT BEFORE OFFSETTING	0,85 kg CO <sub>2</sub> / UNIT	0,79 kg CO <sub>2</sub> / UNIT	0,78 kg CO <sub>2</sub> / UNIT
CO <sub>2</sub> KG/KG ABSORBING AGENT	1,7	1,58	1,56
<b>INSTALLATION ACCESORIES</b>			
OTHER	INTEGRATED HOOK	INTEGRATED HOOK	INTEGRATED HOOK
ABSORSTICK™	15 PCS	2 PCS	0 PCS
GROMMETS	YES	YES	YES
ADHESIVE PADS	NO	NO	NO
<b>PACKAGING INFORMATION</b>			
<b>BOX</b>			
INNER BAG PCS	1	15	15
BOX PCS	15	15	15
BOX GROSS WEIGTH kg	10	10	10
DIM LX W X H mm	478 X 296 X 233	478 X 296 X 233	478 X 296 X 233
<b>PALLET</b>			
PCS	480	480	480
GROSS WEIGHT kg	340	340	340
DIM LX W X H mm	1120 X 1120 X 1100	1120 X 1120 X 1100	1120 X 1120 X 1100

## Dimensions



## Materials



- RECYCLED PLASTIC
- CALCIUM CHLORIDE
- MODIFIED STARCH
- PE-PLASTIC (BACK)
- DUPONT™ TYVEK® HDPE-PLASTIC

## Disposal

Absortech's products are intended for single use. To minimize the environmental impact, we recommend the following procedure for disposal of the used desiccant.

Product dispose to approved waste disposal facility in accordance with local regulations. Calcium chloride is classified as Hazardous Substance according to statement H319 in GHS standard (Causes serious eye irritation) and might therefore be classified as hazardous waste and should be handled accordingly.



RECYCLE

The grey AbsorHook™ (post-consumer PP-plastic) can be separated manually from the product and should be sorted for recycling.

The grey AbsorStick™ (post-consumer PP-plastic) should be sorted for recycling. Note that the AbsorStick™ can also be re-used.

## Dimensioning

The quantity needed will vary depending on various factors such as shipment time, climate conditions, air volume in the container, type of packaging used, cargo type. Contact us for further information.

CONTAINER SIZE		20 ft	40 ft
<b>SHORT DISTANCE ~ 30 DAYS</b>			
ABSORTEL® HANGING-C 0,5 KG	DRY GOODS	10	18
	WET GOODS	14	22
ABSORTEL® HANGING-C 1,0 KG	DRY GOODS	5	9
	WET GOODS	7	11
<b>LONG DISTANCE ~ 60 DAYS</b>			
ABSORTEL® HANGING-C 0,5 KG	DRY GOODS	14	22
	WET GOODS	22	28
ABSORTEL® HANGING-C 1,0 KG	DRY GOODS	7	11
	WET GOODS	11	14

## Availability and Operational Temperature

Stock availability may vary between Absortech regions. Contact Absortech or AbsorPartner for guidance.

Operational temperature: -20 °C to 70 °C



LEARN MORE AT [ABSORTECH.COM](https://www.absortech.com)

Absortech helps you prevent moisture damage during transport. Our promise is to protect your brand, increase your savings and lower the environmental footprint of your logistics processes. We are committed to help businesses like yours implement sustainable solutions to prevent moisture damage.

ABSORPARTNER IN USA

**BUFFERS USA**

DESICCANT-SOLUTIONS.COM  
 JEANINE@BUFFERSUSA.COM  
 OFC: (904) 696-0010, EXT. 2328  
 MOB: (904) 403-7788

